



## MATRIX ACCELERATOR

March 31, 1995

### PRODUCT DESCRIPTION

#### CONTENTS

Matrix Accelerator is a clear, thin liquid containing an aqueous solution of sodium carbonate.

#### USES

An easy to dispense liquid which is used to accelerate and shorten the longer, cold-weather set times of Matrix Mixes as well as other polymer modified cementitious compounds.

#### ADVANTAGES

When used in prescribed amounts, Accelerator will result in 50-100% faster set times. No odor or environmental effects.

#### PREPARATION

Thoroughly mix Matrix Mix, Bonding Additive and Colorant per separate Installation and Mixing procedures contained in Section 12 of Dealer Manual before adding Accelerator to Matrix mixture.

### TECHNICAL DATA

#### CHARACTERISTICS

Color	Clear to Slightly Cloudy
Package	1 Quart Bottle
Use Rate	2-4 Ozs. (Per 40 Lb. Bag)
Solvent	Water
Odor:	None
Flammability Class:	None
Shelf Life:	12 Mos. Unopened
VOC:	0 g/l
Storage:	40°F-90°F

#### COMPOSITON

Water:	Proprietary
Sodium Carbonate:	Proprietary

100%

### PRODUCT APPLICATION

#### APPLICATION

Apply 2-4 ounces of Accelerator per bag of Matrix Mix depending upon temperature, humidity and required set time. Four ounces is the normal amount for temperatures above 55°F with relative humidity in excess of 90% and will result in 50- 100% faster set times. NOTE: More than 4 ounces per Bag may cause efflorescence or the formation of unsightly salts on the finished surface upon exposure to moisture.

#### CLEAN-UP

Clean hands and application tools with detergent and water.

#### HANDLING

Repeated contact with Accelerator may cause redness and dry, cracked skin. In case of eye contact, immediately flush eyes with water for 15 minutes; if irritation persists, seek medical attention. Flush skin with water.